

## Casco® MultiTech

## DECLARATION OF PERFORMANCE

# No. 37210115

1 UNIQUE IDENTIFICATION CODE OF THE PRODUCT-

TYPE:

37210115

2 INTENDED USE/S

EN 15651-3:2012

Sealant for joints in sanitary areas S

3 MANUFACTURER:

Sika Services AG Tüffenwies 16-22 8064 Zürich

4 AUTHORISED REPRESENTATIVE:

5 SYSTEM/S OF AVCP:

System 3

6a HARMONISED STANDARD:

EN 15651-3:2012

Notified body/ies:

1213

37210115 2020.11 , ver. 1 1001

### 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class E	System 3	
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			<del></del>
Resistance to flow	≤ 3 mm	System 3	EN 15651- 3:2012
Loss of volume	≤ 20 %	System 3	
Tensile properties (i.e. elongation)	NF at 60 % elongation	System 3	
Microbiological growth	3	System 3	
Durability	Pass	System 3	

### 8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Anders Beier

Function: General Manager At Farum on 28 May 2021 Name: Jens Berger

Function: Target Market Manager - S&B

At Farum on 28 May 2021

End of information as required by Regulation (EU) No 305/2011

#### RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Casco® MultiTech	EN 15651-1:2012	80287305
Casco® MultiTech	EN 15651-4:2012	67474218

Declaration of Performance Casco® MultiTech 37210115 2010.11 , ver. 1 1001 Template for translation. Only for internal use





20

Sika Services AG, Zurich, Switzerland

37210115

EN 15651-3:2012

Notified Body 1213

Sealant for joints in sanitary areas S

Reaction to fire Class E

Water tightness and air tightness

Resistance to flow  $\leq$  3 mm Loss of volume  $\leq$  20 %

Tensile properties (i.e. elongation) NF at 60 % elongation

Microbiological growth 3

Durability Pass

http://dop.sika.com

### **ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

#### **LEGAL NOTE**

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or endusers of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is effected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.



1001

Sika Danmark A/S

Hirsemarken 5 3520 Farum Denmark www.sika.dk

Declaration of Performance Casco® MultiTech 37210115 2010.11 , ver. 1 1001 Template for translation. Only for internal use

