

PRODUKTDATABLAD

Parkett Elastic Plus

Floor adhesive for most kind of wooden floor.



PRODUKTBESKRIVELSE

Floor adhesive developed for gluing of all type of parquet. SMP based, 1 component.

ANVENDELSE

For wooden floor.

EGENSKABER

- Alkaline stable
- Contains no water
- Elastic glue joint
- Free from solvent
- Suitable for floor heating
- Easy application, can be applied standing with Casco Parkett X press machine

PRODUKTINFORMATION

Kemisk base	SMP (Silane modified polymer)
Emballage	10 liter 2 x 4,2 liter sausage for the Parkett X press machine
Holdbarhed	Bucket and sausage 9 months.
Opbevaringsforhold	The product shall be stored in minimum +10° C in well closed packages. May not be exposed to temperatures below 0° C and above 30° C
Farve	Light brown
Densitet	Approx. 1690 kg/m3
Tørstofindhold vægt	100 %

ANVENDELSE

Forbrug	1 liter / 1-2 m ² .		
Afkast	Material	Trowel	Amount
	Lamella parquet Max. 65% RH	6118	2 m ² /l
	Mosaic / Rod parquet Max. 65% RH	6118	2 m ² /l
	Billet Parquet Max. 65% RH	6119	1 m ² /l
	All type of parquet Over 65% RH up to max. 85% RH	6119	1 m ² /l
Fugtindhold i underlaget	Application temperature: +18°C to +23°C and 30–60% RH. The climate must be maintained for at least 96 h (4d) for optimal result.		
Anvendelsestid	Assembly time, approx. 0–40 minutes.		

BEMÆRK

Alle tekniske data på dette produkt er baseret på laboratorietests. De faktiske forhold varierer og er udenfor vores kontrol.

MILJØ, SUNDHED OG SIKKERHED

Brugeren skal læse det seneste sikkerhedsdatablad (SDS) for produktet, før de bruger det. Sikkerhedsdatabladet indeholder oplysninger og råd om sikker håndtering, opbevaring og bortskaffelse af kemiske produkter og indeholder fysiske, miljømæssige, toksikologiske og andre sikkerhedsrelaterede data.

INSTRUKTION

RECOMMENDED METHOD OF WORKING

ON POROUS SUBFLOORS

Spread the adhesive with a toothed trowel (6118, 6119 or Casco Parkett X press Machine). Don't use more adhesive than necessary to give a good over-wetting during the stated open time. Do not use any kind of primer before applying the adhesive. Firmly press the parquet in the adhesive and check that the whole covering area has full contact with the adhesive. Install the material in the wet adhesive. Do not spread more adhesive than can be used in 20 minutes.

ON NON-POROUS SUBFLOORS

Please contact technical service

FORBEREDELSE AF UNDERLAGET

- Before installing the covering make sure that the subfloor is clean, even and dust free and has an adequate strength, bearing strength, dimensional

stability and is permanent dry.

- The moisture content in the concrete must not exceed 85% RH and the chipboard moisture quota should be 8-12%. If moisture in concrete is higher than 65% RH, but maximum 85% RH please contact technical service for consultation.
- The unevenness should not exceed 3mm over 2m.
- Note that lamella parquet has higher requirements regarding evenness. If the subfloor is concrete it should be steel grinded and carefully vacuumed. If the subfloor is a gypsum based leveling compound, do not grind to avoid dust that will reduce the adhesion. If use of leveling compound, use a quality which has a minimum tensile strength of 2,0 MPa.
- Windows and doors must be installed in the room where the parquet is to be laid, to assure necessary conditions, see above. These conditions must be kept for at least one week prior installing the parquet.
- All other room decorating, like painting and wall paper hanging should be finished before installation.
- The air humidity should be measured by using a hygrometer. It is important that the normal temperature and air humidity of the room are reached before the parquet is installed.
- If there are uncertainties in using the product, contact our Technical Department for advice.

ANVENDELSE

Tools: Toothed trowel e.g. Casco hard metal trowel 6118, 6119 or Parkett X press machine

RENGØRING AF VÆRKTØJ

In case of skin contact, use Sika® Cleaning Wipes-100. Clean application tools with white spirit or Sika® Cleaning Wipes-100.

LOKALE RESTRIKTIONER

Bemærk, som følge af specifikke lokale regler og restriktioner kan den anbefalede anvendelse for produk-

tet variere fra land til land. Se venligst det landespecifikke datablad.

JURIDISK BEMÆRKNING

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not updated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Sika Danmark A/S
Hirsemarken 5
3520 Farum
Tlf. +45 48 18 85 85
www.sika.dk



Produktdatablad
Parkett Elastic Plus
November 2022, Version 01.01
020512020110000001

ParkettElasticPlus-da-DKCASCO-(11-2022)-1-1.pdf