


PRODUCT DATA SHEET

CascoLin Plus

FLOOR ADHESIVE FOR ALL TYPES OF LINOLEUM AND LINOLEUM WITH ACOUSTIC BACKING, CORKMENT OR SIMILAR.



DESCRIPTION

Especially developed for all types of linoleum and linoleum with acoustic backing, corkment or similar. Suitable for needlefelt and textile carpets as well.

USES

- Linoleum
- Linoleum with acoustic backing
- Corkment and likewise
- Needlefelt
- Textile

CHARACTERISTICS / ADVANTAGES

- Strong bond
- Good tack
- Suitable for floor heating
- Contain no APEO
- Suitable for castor wheels
- Suitable in areas with heavy load (eg truck traffic)

PRODUCT INFORMATION

Composition	Copolymer of acryl/EVA dispersion
Packaging	10 liter plastic bucket
Colour	Beige
Shelf life	At least 12 months if stored in minimum +10° C in well closed packages.
Storage conditions	May not be exposed to temperatures below 0° C and above 30° C
Density	Approx. 1200 kg/m ³
Consistency	Thixotropic
Solid content by weight	Approx. 68 %
Viscosity	Approx. 55 000 mPa.s, Brookfield RVT, sp 6, 10 rpm, 25° C

APPLICATION INFORMATION

Consumption	1 liter / 3-3,5 m ² .		
Substrate Temperature	+18°C to +23°C and 20–70% RH. The climate must be maintained for at least 96 h (4d) for optimal result.		
Application Time	Absorbent subfloor, approx. 0–25 min.		
Yield	Material	Absorbent subfloor	Non-absorbent subfloor
	Textile	3-3,5 m ² /l	3-3,5 m ² /l
	Linoleum	3-3,5 m ² /l	3-3,5 m ² /l
	Acoustic	3 m ² /l	
	Corkment	3 m ² /l	

APPLICATION INSTRUCTIONS

RECOMMENDED METHOD OF WORKING

Note; For best result, linoleum shall be installed on a porous subfloor and in wet adhesive.

ON POROUS SUBFLOORS

1. Spread the adhesive with a toothed trowel. Don't use more adhesive than necessary to give a good over-wetting during the stated open time.
2. Install material at once or after a very short open time and rub thoroughly to press out all the air to achieve a good contact between the adhesive and the covering.
- For best result use a carpet roller.
3. Check that the whole covering area has full contact with the adhesive

ON NON-POROUS SUBFLOORS

For best result, create an absorbent subfloor by using a floor levelling compound with low shrinkage and good adhesion to the subfloor. Build up a layer of 2-3 mm. Follow the gluing instructions above "on porous subfloors".

SUBSTRATE PREPARATION

Before installing the covering make sure that the subfloor is clean, even and dust free and has an adequate strength, bearing strength, dimensional stability and is permanent dry.

The moisture content in the concrete must not exceed 85% RH and the chipboard moisture quota should be 8-12%.

CLEANING OF EQUIPMENT

Clean application tools with water before the adhesive has dried. Dried adhesive is dissolved in ethanol.

APPLICATION

Tools: Toothed trowel 6121.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question.

The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Sika Danmark A/S

Hirsemarken 5
3520 Farum
Tlf. +45 48 18 85 85
www.sika.dk



PRODUCT DATA SHEET

CascoLin Plus

October 2019, Version 01.01
020512030110000020

CascoLinPlus-en-DKCASCO-(10-2019)-1-1.pdf